



Female connector axial, screwable with 360deg shielding

PVC, UL, grey, LiYCY	Contact assignment	Number of poles	Coding	Rated voltage [V]	Current rating [A]	Cable length = L [m]	Wire cross section [mm²]	Description	Part No.
 		3		60	3	2	0,25	SAL-8S-RK3-2 / G3	42-10843
								SAL-8S-RK3-3 / G3	42-10844
								SAL-8S-RK3-5 / G3	42-10845
								SAL-8S-RK3-10 / G3	42-10846
		4		30	3	2	0,25	SAL-8S-RK4-2 / G3	42-10851
								SAL-8S-RK4-3 / G3	42-10852
								SAL-8S-RK4-5 / G3	42-10853
								SAL-8S-RK4-10 / G3	42-10854
		8	A	30	1,5	2	0,14	SAL-8S-RK8-2 / G3	42-12190
								SAL-8S-RK8-3 / G3	42-12191
								SAL-8S-RK8-5 / G3	42-12192
								SAL-8S-RK8-10 / G3	42-12193
		3		60	3	2	0,25	SAL-8S-RK3-2 / G2	42-10847
								SAL-8S-RK3-3 / G2	42-10848
								SAL-8S-RK3-5 / G2	42-10849
								SAL-8S-RK3-10 / G2	42-10850
		4		30	3	2	0,25	SAL-8S-RK4-2 / G2	42-10855
								SAL-8S-RK4-3 / G2	42-10856
								SAL-8S-RK4-5 / G2	42-10857
								SAL-8S-RK4-10 / G2	42-10858
		8	A	30	1,5	2	0,14	SAL-8S-RK8-2 / G2	42-12186
								SAL-8S-RK8-3 / G2	42-12187
								SAL-8S-RK8-5 / G2	42-12188
								SAL-8S-RK8-10 / G2	42-12189

Female connector angled

TPU, UL, halogenfree, black, Li9YC11Y									
 		4		30	3	2	0,25	SAL-8S-RKW4-2 / G2	42-12351
								SAL-8S-RKW4-3 / G2	42-12416
								SAL-8S-RKW4-5 / G2	42-12352
								SAL-8S-RKW4-10 / G2	42-12353