



SOCKETS M12 x 1

Front panel mounting, wire termination





Female connector, coupling nut turnable, M16x1.5 thread front panel mounting, wire termination



Contact assignment		Number of poles	Coding	Rated voltage [V]	Current rating [A]	Wire material	Wire cross section [AWG]	Wire length = L [m]	Description	Part No.
Pin 1	Pin 2	4	A	250	4	PVC	24	0,05	SAL-12-FKD4-0,05	43-01378
Pin 3	Pin 4									
Pin 1	Pin 2									
Pin 3	Pin 4									
Pin 5		5	A	60	4	PVC	24	0,05	SAL-12-FKD5-0,05	43-01381
Pin 1	Pin 2									
Pin 3	Pin 4									
Pin 5										
Pin 1	Pin 5	8	A	30	2	PVC	24	0,05	SAL-12-FKD8-0,05	43-01492
Pin 2	Pin 6									
Pin 3	Pin 7									
Pin 4	Pin 8									

Female connector, coupling nut turnable, M12x1 thread , front panel mounting, wire termination



Pin 1	Pin 2	4	A	250	4	PVC	24	0,05	SAL-12-FKD4-0,05-12	43-01493
Pin 3	Pin 4									
Pin 1	Pin 2									
Pin 3	Pin 4									
Pin 5		5	A	60	4	PVC	24	0,05	SAL-12-FKD5-0,05-12	43-01494
Pin 1	Pin 2									
Pin 3	Pin 4									
Pin 5										
Pin 1	Pin 5	8	A	30	2	PVC	24	0,05	SAL-12-FKD8-0,05-12	43-01495
Pin 2	Pin 6									
Pin 3	Pin 7									
Pin 4	Pin 8									