

### CABLE TIES, WHITE & BLACK

#### TECHNICAL SPECIFICATIONS

Material: Nylon 66

Working Temp Range: -40°C – 85°C

UL Flammability Rating: 94V2

Water Absorption (24hr): 1.3%



• The nylon is inert to fungus or mould and is resistant to petrols, oil, grease, and alkalis ECT. Testing of the ties has been based on the full requirements as directed in MILITARY SPECIFICATION MIL-S-23190E and underwrites LABORATORY SPECIFICATION U.L 1565.

• Black cable ties are recommended for general outdoor use and have economic resistance to ultra violet light.

Part Number	Length	Width	Colour	Pack Size
UB100A-BLK	100mm	2.5mm	Black	100
UB100A-NAT	100mm	2.5mm	White	100
UB140A-BLK	144mm	2.5mm	Black	100
UB140A-NAT	144mm	2.5mm	White	100
UB200A-BLK	200mm	2.5mm	Black	100
UB200A-NAT	200mm	2.5mm	White	100
UB200B-BLK	200mm	3.6mm	Black	100
UB200B-NAT	200mm	3.6mm	White	100
UB200C-BLK	200mm	4.6mm	Black	100
UB200C-NAT	200mm	4.6mm	White	100
UB250C-BLK	250mm	4.6mm	Black	100
UB250C-NAT	250mm	4.6mm	White	100
UB300C-BLK	300mm	4.6mm	Black	100
UB300C-NAT	300mm	4.6mm	White	100
UB380C-BLK	380mm	4.6mm	Black	100
UB380C-NAT	380mm	4.6mm	White	100

### CABLE TIE BASES

- Available as 19mm x 19mm or 28mm x 28mm
- Available in Black or White (Natural)

Part Number	Size	Colour
UB19-BLK	19mm x 19mm	Black
UB19-NAT	19mm x 19mm	White
UB28-BLK	28mm x 28mm	Black
UB28-NAT	28mm x 28mm	White

